

Optical Handling and Positioning

Module 1-2
of

Course 1, *Fundamentals of Light and Lasers*



© 2018 University of Central Florida

This text was developed by the National Center for Optics and Photonics Education (OP-TEC), University of Central Florida, under NSF ATE grant 1303732. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.

Published and distributed by
OP-TEC
University of Central Florida
<http://www.op-tec.org>

Permission to copy and distribute

This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. <http://creativecommons.org/licenses/by-nc-nd/4.0>. Individuals and organizations may copy and distribute this material for non-commercial purposes. Appropriate credit to the University of Central Florida & the National Science Foundation shall be displayed, by retaining the statements on this page.




Figure 2-1 *Refractive index of several optical materials as a function of wavelength*




Figure 2-2 *Absorption of light passing through a transparent medium of thickness x*




Figure 2-3 *Transmission characteristics of several optical materials: (a) fused silica, (b) fused quartz, (c) Pyrex, and (d) Zerodur (Source: www.escoproducts.com)*




Figure 2-4 *Reflection and transmission of light incident perpendicular to an air-glass interface*




Figure 2-5 Reflection and refraction of initially unpolarized light containing equal amounts of E_{TE} and E_{TM}




Figure 2-6 *Absence of reflected light at a Brewster angle of incidence when incident light is totally polarized as E_{TM}*




Figure 2-7 *Schematic diagram of a typical vacuum deposition chamber*




Figure 2-8 *Reflection at multiple interfaces with different refractive indices*




Figure 2-9 Reflection at top and bottom interfaces of coating material. Reflected rays 1 and 2 are 180° out of phase, leading to destructive interference and little or no reflected light.




Figure 2-10 *Increase of reflectivity at a specific wavelength λ after reflection at multiple layers of coating*




Figure 2-11 *Reflectance of some metals as a function of wavelength*




Figure 2-12 *Properties of a band pass filter*




Figure 2-13 *Properties of a high pass cut-off filter*




Figure 2-14 *Optical densities of some neutral-density filters*




Figure 2-15 *Percentage of transmission of a specific narrow-band filter*




Figure 2-16 *Transmission characteristics of a radiometric filter showing a nearly uniform transmission between 400 nm and 1000 nm (Image as revised in Fundamentals of Light and Lasers, 3rd Edition)*




Figure 2-17 *Transmission characteristics of a photometric filter*




Figure 2-18 *Transmission characteristics of a safety goggle suitable for protection from CO₂ laser beams*




Figure 2-19 *Cross-sectional view of a triangular optical rail with carriage, adjustable rod, lens support and lens*




Figure 2-20 *Double rectangular optical rail*
(*Courtesy: Newport Corporation*)




Figure 2-21 *Flat-bed bench for optical mounting*







Figure 2-22 *Isolation table with pneumatic legs*




(a) Sliding grip




(b) Spring grip



(c) Swing arm




(d) Threaded ring




(e) Self-centering


Figure 2-23 *Different types of lens/mirror mounts*




(a) Iris diaphragm




(b) Filter holder



(c) Filter holder




(d) Prism holder




(e) Laser holder

Figure 2-24 *Other types of holders for optical elements*




(a) Scissors jack




(b) Sine table

Figure 2-25 *Schematic diagram of a scissors jack and a “sine table”*



(a) Linear translator



(b) Two-dimensional translator

Figure 2-26 *Schematic diagrams of one-dimensional and two-dimensional translators*





Figure 2-27 *Picture of a simple rotational stage and a rotational stage of designed to hold Polaroid sheets*






Figure 2-28 *Combined rotational and translational stage*



(a) Single-slit tilt



(b) Double-angle tilt

Figure 2-29 *One and two-dimensional tilting stages*




Figure 2-30 *A commercial goniometer
(Courtesy: Newport Corporation)*




Figure 2-31 *Schematic diagram for observing surface imperfections on an optical element*




Figure 2-32 *Schematic diagram of an optical setup used to observe internal defects in an optical element*




Figure 2-33 *Experimental setup designed to observe interference fringes on a flat optical element*




Figure 2-34 *Typical interference patterns observed on flat optical test plates of different flatness*