


# Diode Lasers and Their Applications

---

Module 2-6  
of  
Course 2, *Laser Systems and Applications*  
*2<sup>nd</sup> Edition*




© 2018 University of Central Florida

This text was developed by the National Center for Optics and Photonics Education (OP-TEC), University of Central Florida, under NSF ATE grant 1303732. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.


Published and distributed by  
OP-TEC  
University of Central Florida  
<http://www.op-tec.org>

**Permission to copy and distribute**


This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. <http://creativecommons.org/licenses/by-nc-nd/4.0>. Individuals and organizations may copy and distribute this material for non-commercial purposes. Appropriate credit to the University of Central Florida & the National Science Foundation shall be displayed, by retaining the statements on this page.




**Figure 6-1** *Energy-level diagram of a semiconductor diode*  
*a) No voltage; b) forward applied voltage*




**Figure 6-2** *Gallium arsenide laser diode*



**Figure 6-3** *Example of a mounting for a semiconductor laser*




a.




b.


**Figure 6-4** *Methods for active cooling of semiconductor lasers.*  
*a) Side view of a thermoelectric cooler; b) Top view for cooling a diode laser bar.*




**Figure 6-5** *Output of a semiconductor laser as a function of drive current for different operating temperatures*




**Figure 6-6** *Variation of the wavelength of a commercial semiconductor laser with temperature*




**Figure 6-7** *Peak power output of laser diode as a function of peak input current*




**Figure 6-8** *Output spectrum of a gallium arsenide laser at various input current densities for continuous operation of a double heterojunction device at cryogenic temperatures*




**Figure 6-9** *Spectral emission of a commercial semiconductor laser operating at a wavelength near 1550 nm*




**Figure 6-10** *Beam profile from a stripe geometry heterojunction semiconductor laser*




**Figure 6-11** *Diagram of GaAs/AlGaAs laser with oxide stripe geometry*




**Figure 6-12** *Diagram of a semiconductor laser bar*




**Figure 6-13** *Diagram of the side view of: (a) a distributed-feedback semiconductor laser and (b) a distributed Bragg reflector*




**Figure 6-14** *Diagram of one possible configuration of a VCSEL*




**Figure 6-15** *Injection of light into the core of an optical fiber*




**Figure 6-16** *Loss as a function of wavelength for optical fibers*




**Figure 6-17** *Example of a laser-based optical fiber telecommunications system*




**Figure 6-18** *Example configuration for a write-once, read-mostly optical memory*



**Figure 6-19** *Left: Absorption spectrum of Nd:YAG. Right: Emission spectra of pump sources compared with the Nd:YAG absorption spectrum.*



**Figure 6-20** Configuration for an end-pumped, diode pumped intracavity-doubled Nd:YAG laser



**Figure 6-21** *Simple diagram of a fiber laser*