

Integrated Photonics

Figures and Images for Instructors

Module 5

Integrated Photonics Circuits and Systems

Optics and Photonics Series



© 2018 University of Central Florida

This text was developed by the National Center for Optics and Photonics Education (OP-TEC), University of Central Florida, under NSF ATE grant 1303732. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.

Published and distributed by
OP-TEC
University of Central Florida
<http://www.op-tec.org>

Permission to copy and distribute

This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. <http://creativecommons.org/licenses/by-nc-nd/4.0>. Individuals and organizations may copy and distribute this material for non-commercial purposes. Appropriate credit to the University of Central Florida & the National Science Foundation shall be displayed, by retaining the statements on this page.

Optical Transmitter




Figure 5-1 *Optical transmitter device*




Figure 5-2 *Ten-channel LS-PIC transmitter architecture.*
Direction of propagation of light is from right to left. Courtesy of
Infinera




Figure 5-3 *Spectrum of the output light from a transmitter chip, showing the ten channels separated by 200 GHz. Courtesy of Infiner.*




Figure 5-4 *Spectrum of the output light from transmitter chip with equal power in the ten channels. Courtesy of Infinera*

Optical Receiver




Figure 5-5 *Optical receiver device*




Figure 5-6 *Spectrum of the receiver chip output showing the ten channels separated by 200 GHz. Courtesy of Infinera*




Figure 5-7 *Type I ROADM based on planar lightwave circuit (PLC) components*




Figure 5-8 *Transmission for one of the athermal AWG channels at three different temperatures. Courtesy of Enablence*




Figure 5-9 *Chip-to-chip bonded silica AWG and polymer switch/VOA array subassembly for type I ROADMs. Courtesy of Enablence.*




Figure 5-10 $M \times N$ ROADMs based on PLC components




Figure 5-11 *Super high delta silica-on-silicon chip integrating eight AWGs*




Figure 5-12 *Super-high delta polymer chip integrating switches, VOAs, and taps for photodetectors*




Figure 5-13 *Four channel interleaver with phase tuners in the interferometer arms*




Figure 5-14 *Transmission of the four channel tuned interleaver*




Figure 5-15 *Microscope view of monolithically integrated transceiver chip. TX indicates transmitters; RX indicates receivers. Courtesy of Luxtera.*




Figure 5-16 *Rib waveguide structure used in photonic biosensor*




Figure 5-17 *Bimodal waveguide for photonic biosensor*





Figure 5-18 *Left: bimodal waveguide based photonic biosensor. Right: five-sensor chip with light coupled to the chip through gratings.*




Figure 5-19 *Lab-on-a-Chip biosensor platform*




Figure 5-20 *Illustration of cantilever beam*



MEMS Deformable Mirror Schematic




Figure 5-21 *MEMS deformable mirror with a 12 x 12 actuator array. Courtesy of Thorlabs.*




Figure 5-22 *Steerable micromirror array illustration*




Figure 5-23 *Cantilever beam on-off optical switch*